


American Outsole Stitching Machine

Model AOS-A



High speed, quiet, smooth operation

Reliable, low maintenance profile

Versatile, excellent quality performance

Adjustable stitching head height

The results of many years' experience have been combined to develop this awl-fed stitching machine, which offers the capability to produce a wide variety of quality stitching. These include Stitch Aloft, Spaghetti Groove, Slashing Groove, Fudge Stitching, Stitchdown (flexible) Stitching, Bond Welt Stitching with welt application and Moccasin Stitching. Features of the machine include automatic lubrication with fail-safe shutdown, positive automatic lock adjustment extremely accurate heat controls and tension control of thread distribution.

Specifications

Production:	Up to 800 pairs/day depending upon construction, size, and style	Electrical Specifications:	220 Volts, 3 Phase, 60 Cycle (15 Amps) <i>Other electrical specs available upon request</i>
Dimensions:	Width: 36" (914 mm) Depth: 27" (686 mm) Height: 58" (1473 mm) Packed: Domestic: 111 cu. ft. (3.14 m ³) Export: 87 cu. ft. (2.45 m ³)	Pneumatic Specifications:	.25 CFM at 80 pounds per square inch (7 liters per minute at 5.5 Atmosphere)
Weight:	Gross: 1000 lbs. (455 kg) Net: 875 lbs. (398 kg) Export Packed: 1200 lbs. (546 kg)		

American & Schoen
MACHINERY COMPANY

100 Cummings Center, Suite 140A Beverly, MA 01915 U.S.A. tel: 978-524-0168, fax: 978-524-4805
info@asm-schoen.com www.asm-schoen.com



rev 052019