

American Inseam Trimming Machine, Model D (GIT-D)



- **Greater production potential**
- **Smoother performance**
- **Improved safety**
- **Improved exhaust**
- **Quieter operation**
- **Variable speed control**
- **Adjustable head height**
- **Optional - Parts to fit for upper trimming operation**

The important operation of trimming excess upper, lining, box toe and insole rib down close to the inseam of Goodyear Welt shoes has been made faster, safer and quieter. Time and production tested mechanisms have been combined with modern-day technology to produce a machine to meet today's demands.

The speed of the knife and the machine feed have been increased to provide the opportunity for more shoes to be trimmed at a faster rate.

The machine is provided with a variable speed control which allows simple change of the feed

wheel and cutter speed to accommodate the operator experience level as well as the type shoe being trimmed.

Safety switches have been added which stop the drive motor instantly if certain machine guards are opened, making for a safer operation.

The need for opening the knife guard to clear obstructions is reduced greatly by the addition of an improved exhaust system which operates more efficiently and quieter. A separate

GIT-D

container is provided for the collection of the scrap material. This container can be placed to the left, the right or behind the machine depending on the space requirements.

A separate motor drives the oscillating knife sharpening mechanism and can be activated on command. Machine control switches and adjustments have been

located conveniently with attention given to ease of access. The machine is easily adjusted up or down so as to accommodate the height of the operator.

The above features combined with time-proven and time-tested principles provide a smoother, quieter, safer and higher-performance machine.

Specifications:

Machine Dimensions		
<i>Height</i>	68"	172.5cm
<i>Width</i>	28.5"	72.5cm
<i>Depth</i>	28.5"	72.5cm
<i>Net Weight</i>	800 lbs.	363Kg

Exhaust System Dimensions		
<i>Height</i>	52"	132cm
<i>Width</i>	20"	50cm
<i>Depth</i>	26"	66cm
<i>Net Weight</i>	100 lbs.	45Kg

Motors			
	<i>CUTTER & FEED</i>	<i>CUTTER GRINDER</i>	<i>EXHAUST SYSTEM</i>
<i>Power</i>	1.5 hp (1.1 kW)	0.5 hp (0.3 kW)	0.5 hp (0.3 kW)
<i>Frequency</i>	60 Cycle	60 Cycle	60 Cycle
<i>Voltage</i>	200 • 230 • 460	200 • 230 • 460	200 • 230 • 460
<i>Amperage</i>	6.0 • 5.2 • 2.6	2.3 • 2.0 • 1.0	2.3 • 2.0 • 1.0
<i>Frequency</i>	50 Cycle	50 Cycle	50 Cycle
<i>Voltage</i>	220 • 380	220 • 380	220 • 380
<i>Amperage</i>	4.2 • 2.5	2.6 • 1.5	2.6 • 1.5

American & Schoen
 MACHINERY COMPANY
a subsidiary of Schön & Sandt AG